



POWERED AIRE INC.

www.poweredaire.com

**MODEL: ETD - Dual Speed Unheated
Climate Control Eight Ten Door
Door Height: Up to Ten Feet**

PRODUCT DATA DUAL SPEED UNITS (H) HIGH SPEED (L) LOW SPEED

Model	ETD 1-36	ETD 1-42	ETD 1-48	ETD 1-60	ETD 2-60	ETD 2-72	ETD 2-84	ETD 2-96	ETD 3-108	ETD 3-120	ETD 3-132	ETD 4-144
Nozzle width inches	36	42	48	60	60	72	84	96	108	118	133	145
Max. FPM at Nozzle	H 4218 L 2837	H 4218 L 2837	H 4218 L 2837	H 4218 L 2837	H 4218 L 2837	H 4218 L 2837	H 4218 L 2837	H 4218 L 2837	H 4218 L 2837	H 4218 L 2837	H 4218 L 2837	H 4218 L 2837
Max. CFM at Nozzle	H 2899 L 1950	H 3384 L 2276	H 3867 L 2601	H 4374 L 2792	H 5050 L 3252	H 5803 L 3903	H 6766 L 4551	H 7732 L 5201	H 8702 L 5853	H 9668 L 6503	H 10853 L 7155	H 11606 L 7806
Avg. FPM at Nozzle	H 3695 L 2487	H 3169 L 2133	H 2771 L 1865	H 2218 L 1493	H 3315 L 2231	H 3696 L 2488	H 3169 L 2133	H 2773 L 1866	H 3702 L 2486	H 3174 L 2134	H 2792 L 1885	H 3696 L 2488
CFM at Nozzle	H 2541 L 1710	H 2532 L 1696	H 2559 L 1721	H 2528 L 1703	H 3812 L 2565	H 5082 L 3420	H 5063 L 3382	H 5081 L 3417	H 7623 L 5130	H 7614 L 5127	H 7589 L 5104	H 10164 L 6840
Outlet Velocity Uniformity	95%	93%	92%	91%	94%	95%	93%	92%	95%	94%	94%	95%
Number of Motors	1	1	1	1	2	2	2	2	3	3	3	4
Horse Power	3/4	3/4	3/4	3/4	3/4	3/4	3/4	3/4	3/4	3/4	3/4	3/4
Weight (Lbs)	90	97	104	117	147	169	187	203	245	274	290	338

Sound Level: High Speed 63 dba Low Speed 56 dba
Sound level measured 10 feet from unit in a free field based on a 1 motor unit.

Single Phase Motor Voltage Available: 120 208/230 480 575
Amp Draw Per Motor: 8.0 3.6 2.2 1.5
 ** Nozzle width equals door width.
 ** For three phase motors consult factory.
 ** For unit over twelve feet long consult factory.

